


Always check the website for the most updated specifications: www.americh.com






92° 10 1½ 23 1½ Dia. 26 28


Tub pictured with optional waste & overflow.

All bathtub dimensions are $\pm 1/2$ ".

Builder Series







DIMENSIONS

48" x 48" x 28" (1219 x 1219 x 711 mm) Whirlpool Operating Gallons = 90 (Liters = 341) Gallon to Overflow = 118 (Liters = 447)

MATERIAL: Acrylic (All Americh Standard Colors)


TUB FLOOR: Textured UNDERMOUNT: Yes

Advise Americh when ordering to ensure there are no issues with deck mounted controls.

Americh recommends one 20 amp ground fault circuit interrupter


Always take dimensions directly from the unit.

Platinum Series



Combination

(pump and blower location only)



(GFCI) for each power supply provided with the bathtub. OPTIONAL ACCESSORIES

Chromatherapy*

• Grab Bars: 9" * - 14" - 16"

ELECTRICAL REQUIREMENTS

High Density Insulation*

• iBath Sound System

• Inline Heater (whirlpool only)

Jets: Additional or Rotary*

• Lo Profile Tub Edge

• Ozone System (whirlpool and/or Airbath only)

• Pillows: Angle* - 12"

• Remote Control Upgrade (select series only)

Serenity Soak (tub only)

Syllent Pump with Heated Air*

• Thermal Comfort System

• Tile Flange Kit

Trim Kit Upgrade*

Waste & Overflows Upgrades

Cable Drive Waste & Overflow*


PVC Waste & Overflow⁺


Linear Waste & Overflow

(*) Standard on Platinum Series


(+) Standard on Luxury Series

Airbath System II





Airbath System III







- ACCESS PANEL (MINIMUM 16" X 20")

INSTALLATION TIPS

- Install according to Owner's Manual and local codes.
- Airbath III units may be 11/2" 21/2" higher than stated.
- Any whirlpool or Airbath® unit requires an access panel.
- Hot water supply should be 65-75% of tub capacity or greater.
 Always consult your local plumber for recommendations as
- Always consult your local plumber for recommendations as installations will vary.
- Cut-out dimensions: 46" x 46"
- The combination of multiple systems and options may require components to stick out and/or be remotely installed in the field.

CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- Canadian Standards Association (CSA)
- ANSI Z124.1 ANSI A112-19.7
- ANSI A112.19.8

Contact Americh for additional approvals.

