





SHOWERHEAD

- H₂Okinetic Technology® Showerhead
- 5-Spray Setting Showerhead
- Touch-Clean® Nozzles
- Push Button Diverter



Submitted Model No.: _____

Specific Features: _____



▲ Designate proper finish suffix

Spray Pattern

- H₂Okinetic Spray
- Full Body Spray
- Massage Spray
- Full Spray w/ Massage
- Pause

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-B-52669 Rev. A

STANDARD SPECIFICATIONS:

- Maximum 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa.
- Change spray modes with push button.
- ABS showerhead with five spray settings – not a positive shut-off.
- Metal ball connector for durability, easy installation.
- Ball connector swivel angle is 44° (22° per side).
- Standard 1/2"-14 NPT pipe fitting.

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH

- ASME A112.18.1 / CSA B125.1
- EPA WaterSense®



55 E. 111th Street, Indianapolis, Indiana 46280
350 South Edgeware Road, St. Thomas, Ontario Canada N5P 4L1
© 2016 Masco Corporation of Indiana