

#53438 FLAPPER

INSTRUCTIONS

1. TURN OFF WATER TO TOILET, FLUSH TOILET
2. REMOVE OLD FLAPPER (SEE A & C)
3. INSERT TIP WITH SMALLEST HOLE (D) INTO BOTTOM OF NEW FLAPPER (E)
4. INSTALL NEW FLAPPER ON FLUSH VALVE
5. INSTALL NEW LIFT CHAIN OR STRAP INTO FLUSH ARM (SEE D)
6. TURN ON WATER, ALLOW TOILET TANK TO FILL

ADJUSTMENTS

IF FLUSH IS NOT ADEQUATE, INSERT TIP WITH NEXT LARGEST HOLE AND THEN FLUSH THE TOILET. REPEAT THIS PROCESS UNTIL YOU LOCATE THE TIP THAT ALLOWS THE SHORTEST FLUSH WITHOUT HAVING TO DOUBLE FLUSH TO REMOVE THE CONTENTS OF YOUR BOWL.

(NOTE; THE LARGER THE HOLE IN THE TIP THE SHORTER THE FLUSH WILL BE. SEE CHART BELOW FOR APPROXIMATE TIME FLAPPER WILL STAY OPEN.)

BROWN	1.5 Seconds
RED	2.0 Seconds
WHITE	3.6 Seconds
GREEN	4.7 Seconds
ORANGE	5.8 Seconds

